EU SYN-600E-30

- Switching time ≤100ms
- Supporting self-feeding and self-restoring
- Modular design, easy to install and maintain
- Automatically switch to the intermediate state when the power supply is missing



POWER-ING TOMO-RROW

GROWATT

en.growatt.com

Datasheet	EU SYN 600E-30
Input Data(AC/Grid)	
Max. AC apparent power	330kVA
Nominal AC voltage	380/400/415V
AC grid frequency	50Hz/60Hz
Max. input current	600A
AC grid connection type	3P4W+PE
Input Data(GEN)	
Max. AC apparent power	330kVA
Nominal AC voltage	380/400/415V
AC grid frequency	50Hz/60Hz
Max. input current	600A
AC grid connection type	3P4W+PE
Output Data(Load)	
AC nominal power	300kW
Max. AC apparent power	330kVA
Nominal AC voltage/range	380/400/415V
Max. output current	600A
General Data	
Dimensions (W/H/D)	700/900/376mm
Weight	65kg
Operating temperature range	-25℃ ~ 60℃ (>50℃ derating)
Altitude	4000m
Cooling	Nature convection
Protection degree	IP66
Installation	Wall Mountable

SHENZHEN GROWATT NEW ENERGY CO.,LTD All rights reserved. All specifications are subject to change without notice.

SHENZHEN GROWATT NEW ENERGY CO.,LTD.
T: + 86 755 2747 1900 F: + 86 755 2749 1460
A: 4-13/F,Building A,Sino-German(Europe)Industrial Park,Hangcheng Ave,Bao'an District,Shenzhen,China
E: info@ginverter.com